

## ヘルマート変換計算書

重心変換前      105.000      98.000      回転角    60-31-18      距離比率    1.000000  
 変換後      23601.126      54712.346

平均二乗誤差      0.002      0.001

測点名	X座標	Y座標	-->	測点名	X座標	Y座標	E X	E Y	E L
AA	100.000	100.000		A-	23596.931	54708.978	-0.007	0.000	0.007
BB	100.000	96.000		B-	23600.402	54707.012	0.004	-0.003	0.005
CC	110.000	96.000		C-	23605.326	54715.712	0.002	0.002	0.003
DD	110.000	100.000		D-	23601.844	54717.682	0.001	0.001	0.002

測点名	X座標	Y座標	-->	測点名	X座標	Y座標
EE	114.380	106.965		E-	23597.937	54724.924
FF	110.017	113.863		F-	23589.785	54724.520
GG	107.423	106.729		G-	23594.719	54718.751
HH	101.645	112.802		H-	23586.589	54716.709
II	93.627	104.017		I-	23590.291	54705.406
JJ	91.976	92.579		J-	23599.436	54698.340
KK	100.289	87.567		K-	23607.890	54703.111
LL	105.478	91.635		L-	23606.901	54709.630
MM	110.607	88.275		M-	23612.351	54712.441
NN	114.439	92.697		N-	23610.388	54717.954
OO	114.439	99.359		O-	23604.588	54721.232
PP	103.119	108.026		P-	23591.472	54715.642
QQ	98.108	103.663		Q-	23592.804	54709.133
RR	94.983	96.706		R-	23597.323	54702.989