

オフセット計算

	測点名	X座標	Y座標	方向角
IP	B	-50.000	400.000	
基線の原点	A	100.000	100.000	116-33-54

測点名	X座標	Y座標	距離	支距
b	-50.000	400.000	335.410	0.000
a	100.000	100.000	0.000	0.000
a1	0.000	100.000	44.721	89.443
aR10	0.000	99.700	44.453	89.577
aL10	0.000	100.300	44.990	89.309
2	20.000	101.000	36.672	71.107
2R10	20.000	100.700	36.403	71.241
2L10	20.000	101.300	36.940	70.973
3	40.000	101.200	27.906	53.129
3R10	40.000	100.900	27.638	53.263
3L10	40.000	101.500	28.174	52.995
b1	60.000	100.600	18.425	35.509
bR10	60.000	100.300	18.157	35.643
bL10	60.000	100.900	18.694	35.375
KA1	100.000	100.000	0.000	0.000
KE1	156.906	180.880	46.892	-87.069
KE2	158.871	227.929	88.095	-109.867
KA2	-14.067	351.581	276.033	-10.486
KA1 2	113.962	114.319	6.563	-18.892
KA1 3	127.339	129.184	13.877	-37.504
KA1 4	139.481	145.065	22.651	-55.467
KA1 5	149.632	162.279	33.508	-72.244
KA1 7	160.469	200.526	62.871	-99.042
KA1 8	160.059	220.489	80.909	-107.603
KA1 9	155.704	239.976	100.287	-112.422
KA1 10	147.768	258.305	120.230	-113.521
KA1 11	136.824	275.018	140.073	-111.207

測点名	X座標	Y座標	距離	支距
KA1 12	123.452	289.867	159.334	-105.887
KA1 13	108.192	302.775	177.704	-98.011
KA1 14	91.518	313.801	195.023	-88.028
KA1 15	73.824	323.109	211.261	-76.365
KA1 16	55.422	330.932	226.488	-63.404
KA1 17	36.553	337.554	240.849	-49.489
KA1 18	17.394	343.289	254.547	-34.917
KA1 19	-1.924	348.467	267.817	-19.954